



Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifiers

Product name : Sanonda Herbicide Trifluralin 480EC
Active ingredient : Trifluralin
Product code : 7101

1.2. Other means of identification

IUPAC name:
2,6-dinitro-*N,N*-dipropyl-4-(trifluoromethyl)aniline.

1.3. Recommended use of the chemical and restrictions on use

A pre-emergence herbicide for the control of annual grasses and certain broadleaf weeds in certain horticultural and agricultural crops as listed in the Direction for Use Table

1.4. Details of the supplier of the safety data sheet

Sanonda (Australia) Pty Ltd (ABN 23 059 813 973)
Address: Suite 822, St Kilda Road Towers, No. 1 Queens Road, Melbourne,
Victoria 3004 Australia.

TEL: +61 3 9863 8081
FAX: +61 3 9863 8083
email@sanonda.com

1.4. Emergency telephone number

Emergency number : +61 3 9863 8081

SECTION 2: Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification	Acute Toxicity (Oral) Category 4, Aspiration Hazard Category 1, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Carcinogenicity Category 2, Specific Target Organ Toxicity -Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 1
Legend:	Classified by Chemwatch;



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanondaaz.com
www.sanondaaz.com

	Classification drawn from HCIS; Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		
Label elements			
Hazard pictogram(s)			
Signal word	Danger		

Hazard statement(s)

H302 Harmful if swallowed.

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
------------------	--



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

P331	Do NOT induce vomiting.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
Precautionary statement(s) Storage	
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
Precautionary statement(s) Disposal	
P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3: Composition/information on ingredients

Chemical Characterization	Liquid					
	Ingredients	Name	CAS	Concentration,g/L	TWA (mg/m3)	STEL (mg/m3)
		Trifluralin	1582-09-8	480g/L	not set	not set
		Liquid hydrocarbon	secret	460g/L	not set	not set
		Other non hazardous ingredients	secret	to 100	not set	not set

Liquid hydrocarbon secret 460g/L not set not set Other non hazardous ingredients secret to 100 not set not set
This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.oz.com
www.sanonda.oz.com

SECTION 4: First aid measures

Description of first aid measures

	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water.
Eye Contact	<ul style="list-style-type: none"> ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
in Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
 www.sanonda.com

SECTION 5: Firefighting measures

Extinguishing media

- › Foam.
- › Dry chemical powder.
- › BCF (where regulations permit).
- › Carbon dioxide.
- › Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> › Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Fire Fighting	<ul style="list-style-type: none"> › Alert Fire Brigade and tell them location and nature of hazard. › Wear full body protective clothing with breathing apparatus. › Prevent, by any means available, spillage from entering drains or water course. › Use water delivered as a fine spray to control fire and cool adjacent area. › Avoid spraying water onto liquid pools. › DO NOT approach containers suspected to be hot. › Cool fire exposed containers with water spray from a protected location. › If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	<ul style="list-style-type: none"> › Combustible. › Slight fire hazard when exposed to heat or flame. › Heating may cause expansion or decomposition leading to violent rupture of containers. › On combustion, may emit toxic fumes of carbon monoxide (CO). › May emit acrid smoke. › Mists containing combustible materials may be explosive. <p>Combustion products include: carbon dioxide (CO₂) hydrogen fluoride nitrogen oxides (NO_x) other pyrolysis products typical of burning organic material.</p> <p>CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</p>
HAZCHEM	•3Z



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanondaaz.com
 www.sanondaaz.com

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard - contain spillage. Slippery when spilt. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
 www.sanonda.com

SECTION 7: Handling and storage

Precautions for safe handling

<p>Safe handling</p>	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
<p>Other information</p>	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

<p>Suitable container</p>	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
<p>Storage incompatibility</p>	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
trifluralin	1.2 mg/m ³	13 mg/m ³	78 mg/m ³
Ingredient	Original IDLH	Revised IDLH	
trifluralin	Not Available	Not Available	
liquid hydrocarbons	Not Available	Not Available	

Occupational Exposure Banding

Ingredient	Occupational Exposure Banding rating	Occupational Exposure Banding limit
Trifluralin	E	≤ 0.01 mg/m ³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved</p>
-------------------------	--

controls	<p>respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.</p> <p>An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <p>Type of Contaminant: Air Speed:</p>											
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)										
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)										
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)										
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)										
	<p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table>		Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
	Lower end of the range	Upper end of the range										
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents											
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity											
3: Intermittent, low production.	3: High production, heavy use											
4: Large hood or large air mass in motion	4: Small hood-local control only											
<p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction</p>												



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanondaos.com
 www.sanondaos.com

	<p>of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>
--	--

Personal protection	
---------------------	--

Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. ▶ Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. ▶ Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. ▶ Alternatively a gas mask may replace splash goggles and face shields. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
-------------------------	---



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
 www.sanonda.com

Skin protection	See Hand protection below
Hands/feet protection	<p>· Elbow length PVC gloves</p> <p>NOTE:</p> <p>· The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</p> <p>· Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</p> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> · Excellent when breakthrough time > 480 min



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanonda.oz.com
 www.sanonda.oz.com

	<ul style="list-style-type: none"> · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> · Overalls. · P.V.C apron. · Barrier cream. · Skin cleansing cream. · Eye wash unit.

SECTION 9: Physical and chemical properties

Form	Liquid
Appearance	Orange coloured liquid with characteristic hydrocarbon odour.
Melting point/freezing point	No specific data. Liquid at normal temperatures.



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

Volatiles:	No specific data. Expected to be low at 100°C.
Specific Gravity	1.08 – 1.10 at 20 oC
Solubility in Water	Emulsifiable.

SECTION 10: Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition	See section 5.

SECTION 11: Toxicological information

Information on toxicological effects

Inhaled	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Inhalation hazard is increased at higher temperatures.</p>
Ingestion	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p>
Skin Contact	<p>Skin contact with the material may produce severe damage to the health of the individual; systemic effects may result following absorption and these may be fatal.</p> <p>There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material The material may</p>



SANONDA
 (AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
 1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
 www.sanonda.com

	<p>accentuate any pre-existing dermatitis condition</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
Eye	<p>This material can cause eye irritation and damage in some persons.</p>
Chronic	<p>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.</p> <p>Chronic exposure to nitro compounds of aromatic hydrocarbons have been known to cause liver and kidney damage.</p> <p>Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.</p> <p>Most arylamines are very toxic to the blood cell-forming system, and they produce methaemoglobinaemia in humans. High doses congest the spleen and then cause formation of sarcomas (a type of malignant tumour).</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.</p> <p>Oral administration of C20-24 alkenes has not been shown to exhibit significant toxicity in humans.</p> <p>Animal testing to see whether nitrites caused cancer proved inconclusive.</p>



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

	Endpoint	Test duration (hr)	Test species		
Sanonda Herbicide Trifluralin 480EC	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
Trifluralin	BCF	672h	Fish	172-598	7
	LC50	96h	Fish	0.045mg/l	Not Available
	EC50	72h	Algae or other aquatic plants	0.102-0.595mg/l	4
	EC50	96h	Algae or other aquatic plants	0.214mg/l	4
	EC50	48h	Crustacea	0.1mg/L	5
	NOEC(ECx)	72h	Crustacea	0.00005mg/l	4

	Endpoints	Test duration	Results	Source
liquid hydrocarbons	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan)- Bioconcentration Data 8. Vendor Data			

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence in water / soil	Persistence in air
Trifluralin	HIGH	HIGH



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

Bioaccumulative potential

Ingredient	Bioaccumulation
trifluralin	MEDIUM (BCF = 945)
Mobility in soil	
Ingredient	Mobility
trifluralin	LOW (KOC = 9682)

SECTION 13: Disposal considerations

Waste treatment methods

Product / packaging disposal	<ul style="list-style-type: none"> ▸ DO NOT allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority. ▸ Recycle wherever possible or consult manufacturer for recycling options. ▸ Consult State Land Waste Authority for disposal. ▸ Bury or incinerate residue at an approved site.
------------------------------	--

SECTION 14: Transport information

Labels Required

Marine Pollutant	
HAZCHEM	•3Z

Land transport (ADG)

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains trifluralin)



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

Transport hazard class(es)	Class	9
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	274 331 335 375 AU01
	Limited quantity	5 L

Air transport (ICAO-IATA / DGR)

UN number	3082	
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains trifluralin)	
Transport hazard class(es)	ICAO/IATA Class	9
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	9L
Packing group	III	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A97 A158 A197 A215
	Cargo Only Packing Instructions	964
	Cargo Only Maximum Qty / Pack	450 L
	Passenger and Cargo Packing Instructions	964
	Passenger and Cargo Maximum Qty / Pack	450 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y964
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains trifluralin)



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

Transport hazard class(es)	IMDG Class	9
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-A, S-F
	Special provisions	274 335 969
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Ingredients	Group
Trifluralin	Not Available
liquid hydrocarbons	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
trifluralin	Not Available
liquid hydrocarbons	Not Available

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

<p>Trifluralin is found on the following regulatory lists: Australia Chemicals with non-industrial uses removed from the Australian Inventory of Chemical Substances (old Inventory) Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals.</p>	<p>Chemical footprint project-chemicals of high concern list: International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic.</p>
---	--

liquid hydrocarbons is found on the following regulatory list: not applicable

National Inventory Status



SANONDA
(AUSTRALIA) PTY LTD

Ph: 03 9863 8081/ Fax: 03 9863 8083

Suite 822, St Kilda Road Tower,
1 Queens Road, Melbourne, VIC 3004

email@sanonda.com
www.sanonda.com

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (trifluralin)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (trifluralin)
USA - TSCA	No (trifluralin)
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	<i>Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</i>

SECTION 16. OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

All due care and skill, so far as practicable, has been applied in the preparation and collation of the information in this SDS. Each user of the Product named in this SDS should read and consider the information contained in this SDS in the context of how the Product will be stored, handled, used or applied in the workplace. In all circumstances, it is the responsibility of the user of the Product to ensure that they have sought out the relevant safety data appropriate to their particular situation. Nothing contained in this SDS shall be construed as a representation or recommendation to the user about the suitability or otherwise of the Product named in this SDS for the user's particular situation. If the user requires any clarification or further information, the user should contact Sanonda (Australia) Pty Ltd.

National Poisons Information Centre: Dial 13 11 26 (from anywhere in Australia)

Please read all labels carefully before using product.

Date of Issue: April 08, 2025.